



## A problem has occurred

2026-05-31 14:08:25

### Error message:

This license has expired on 2026-05-30.

### License Information:

|                        |   |
|------------------------|---|
| License serial no:     | 3916  |
| Licensee:              | Adeona Oy   |
| Product:               | PDFReactor Web Service  |
| Version:               | 12.0  |
| License Type:          | CPU   |
| Amount:                | 12 Thread(s)  |
| Maintenance Exp. Date: | 2026-05-30  |
| Expiration Date:       | 2026-05-30  |
| Purchase Date:         | 2015-11-18  |
| Conditions:            | [This license is for use on development systems only. It may not be used on staging or productive systems of any kind.] |
| Sign Date:             | 2025-06-02 15:12  |

**REKA**by **Nexans**ISO 45001, ISO 14001 and ISO 9001 certified company  
REACH and RoHS compliant products

2026-05-31 14:08:25

MK-HF C / H07Z1-R

Asennusjohto-HF

450/750 V



Asennusjohdin kiinteään sisä- ja ulkoasennukseen. Ei maahan eikä suoraan betonivaluun. Soveltuu rakennusten uloskäytäviin ja lääkintätiloihin standardin SFS 6000 vaatimusten mukaisesti. Asennus on tehtävä kansallisten asetusten ja määräysten mukaisesti. Kaapeli on halogeeniton ja paloa levittämätön CPR-luokassa Cca-s1,d1,a1.

|  |   |
|--|---|
| <b>Standardit</b>                                  | EN 50525-3-31                                   |
| <b>Käyttätyminen palossa</b>                       | Cca-s1,d1,a1; EN 13501-6, EN 50575:2014+A1:2016 |
| <b>Johdin</b>                                      | Pyöreä kupariköysi, EN/IEC 60228 luokka 2       |
| <b>Eriste</b>                                      | UV-suojattu polyolefiinisekoite                 |
| <b>Johtimien tunnistaminen</b>                     | Keltavihreä                                     |
| <b>Tuotekoodi</b>                                  | 1140968   |
| <b>Tuotteen koko</b>                               | 300 GNYE H07Z1-R                                |
| <b>Kaapelin nimellishalkaisija mm</b>              | 25  |
| <b>Kaapelin nimellispaino kg/km</b>                | 2947  |
| <b>Asennuksen aikana, kaapeli cm</b>               | 20  |
| <b>Lopullisessa asennuksessa, kaapeli cm</b>       | 8   |
| <b>Maksimi DC resistanssi, johdin 20 °C Ω/km</b>   | 0,0601  |
| <b>Max. johdinlämpötila käytössä °C</b>            | 70  |
| <b>Max. johdinlämpötila, oikosulku max. 5 s °C</b> | 160   |
| <b>Min. kaapelin käsittelylämpötila °C</b>         | -15   |
| <b>Vakiopakkaus m</b>                              | Kela 250  |
| <b>Sähkönumero</b>                                 | 0406918   |
| <b>EAN-koodi</b>                                   | 6438176309292                                   |



REALOBJECTS

PDFReactor<sup>®</sup>

## Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.3.2 (17644). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

**NOTE:** Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

## Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

## About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit [www.pdfreactor.com](http://www.pdfreactor.com)